Apparatus fo	or synthesizing analog signals in PCM.
Patent Number; Publication date; Inventor(s); Applicant(s);; Requested Patent; Application Number; Priority Number(s); IPC Classification; EC Classification; Equivalents;	EP0337458 1989-10-18 OGAWA TORU; SATO SEIICHI NAMCO LTD (JP) IJ EP0337458; A3, B1 EP19890106631 19890413 JP19880090575 19880413 G10H1/12; G10H7/00; G10H7/08 G10H7/00 CA1309775, DE68912380D, DE68912380T; ES2050176T, IJ JP1261909, JP2970907B2; KR9702239, IJ US5050474
channels being read apparatus includes a memory for each channels respective channels cut-off frequency b.	Abstract n provides an analog signal synthesizing apparatus including a waveform memory for storing a plurality of CM data sampled with different sampling frequencies, the amount of PCM data corresponding to plural from the waveform memory and used to synthesize the analog signals. The analog signal synthesizing n oversampling device for shifting the sampling frequency of said PCM data read from said waveform annel toward the side of high frequency; a summing device for summing the oversampled PCM data for el; a D/A converter for converting the summed data into an analog signal; and a low-pass filter for setting ased on the sampling frequency shifted to the side of high frequency and for all interests as the interest of the sampling frequency shifted to the side of high frequency and for all interests as the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the interest of the sampling frequency shifted to the side of high frequency and for all interests the sampling frequency and sample sample shifted to the side of high frequency and for all interests the sample sam
III CICCO III DIE F CIVI	data from the synthesized analog signal. The elimination of the aliasing noise included in the PCM data for ed out at the common low-pass filter. Data supplied from the esp@cenet database - 12

•

Dotont N.,L	
Patent Number:	EP0337458, A3, B1
Publication date:	1989-10-18
Inventor(s):	OGAWA TORU; SATO SEIICHI
Applicant(s)::	NAMCO LTD (JP)
Requested Patent:	KR9702239
· · · · · · · · · · · · · · · · · · ·	EP19890106631 19890413
Priority Number(s):	JP19880090575 19880413
IPC Classification:	G10H1/12 ; G10H7/00 ; G10H7/08
EC Classification:	<u>G10H7/00</u>
Equivalents:	CA1309775, DE68912380D, DE68912380T, ES2050176T, <u>JP1261909</u> , JP2970907B2, <u>JUS5050474</u>
	Abstract
analog signals as PC channels being read apparatus includes a memory for each chann a cut-off frequency bincluded in the PCM	Abstract In provides an analog signal synthesizing apparatus including a waveform memory for storing a plurality of CM data sampled with different sampling frequencies, the amount of PCM data corresponding to plural from the waveform memory and used to synthesize the analog signals. The analog signal synthesizing in oversampling device for shifting the sampling frequency of said PCM data read from said waveform annel toward the side of high frequency; a summing device for summing the oversampled PCM data for el; a D/A converter for converting the summed data into an analog signal; and a low-pass filter for setting assed on the sampling frequency shifted to the side of high frequency and for eliminating aliasing noises data from the synthesized analog signal. The elimination of the aliasing noise included in the PCM data for elimination low-pass filter.